

Bid To Furnish Materials

To Furnish and deliver materials to
Topeka Correctional Facility
Topeka, Kansas

3500' 12' class 2 chain link fence plus 1 barbwire continuous, 1-12'x16' gate.

Supply all parts, bolts, brackets, rails and posts to construct 3500' of 12' high chain link fence. Fence posts will be set in concrete with a 4" concrete slab at the base of the fence with ½" diameter "J" rods set in concrete to secure bottom rail. Corner posts and line posts to have barbwire arms with one strand barbwire. (Razor ribbon by others). Top rail continuous thru barb arms, middle and bottom rail between corner and line posts with all necessary construction parts. All parts to be galvanized. Pipe to be schedule 40 1.80 oz. coating.

Itemized parts list must be submitted with Bid.

Material list herewith is what is needed for job but not limited to.

Material List

3500 ' – 2 x 9 Ga. x 12' high class 2 galvanized chain link fence fabric.

38 ea. 4" x 16' corner posts w/connections, rail ends, barb arm top (3 strand), clamps, nuts and bolts.

315 ea. 2 3/8" x 15' line posts w/connections, rail ends, barb arm top (3 strand), clamps, nuts and bolts.

10,500 LN FT 1 5/8" top, middle and bottom rail with sleeves.

3500 ea. 9 ga. Galvanized steel prison ties for 2 3/8" line posts.

6500 ea. 9 ga. Galvanized steel prison ties for 1 5/8" rails.

4 ea. 1320' rolls 12 ga. class 3 coating 2 point 2.4" spacing barbwire.

800 ea. "J" rod 1/2" diameter to hold bottom rail into 4" concrete slab.

1 ea. 12' high x 16' wide double swing gate with standard hardware to 4" posts with (V style barb arms – 4 per)